

X-treme Brush Cutter



XBC162672

Our X-treme Brush Cutter is an ideal attachment for tough clearing applications. The cutter comes in a 60" or 72" cutting width. It is equipped with bidirectional blades, powered by a high torque motor and features a 100-hp Omni gear box. A flow of 14–20 gpm is required on the low flow, 20–30 gpm on the mid flow, and 30–50 gpm on the high flow. The one year warranty does not cover the blades or hoses. (Please see page 65 of the catalog for full warranty).



X-treme High Flow Brush Cutter 30 GPM – 50 GPM

- 6" cutting capacity
- 1/4" deck with sides reinforced with 3/8" AR400
- 100 HP Planetary Drive with 6 bolt flange blade carrier
- 3 Bidirectional blades made with 5/8" AR400
- Gear motor with 3800 PSI external relief valve
- Requires a case drain
- Available in 60" or 72" cutting width

X-treme Mid Flow Brush Cutter 20 GPM – 30 GPM

- 6" cutting capacity
- 3/16" deck with sides reinforced with 3/8" AR400
- 1/4" deck optional upgrade
- 100 HP right angle gear box with 6 bolt flange blade carrier
- 3 bidirectional blades made with 5/8" AR400
- High torque motor with 3000 PSI external relief valve

X-treme Low Flow Brush Cutter 14 GPM – 20 GPM

- 5" cutting capacity
- 3/16" Deck with sides reinforced with 3/8" A36
- 1/4" deck optional upgrade
- 100 HP right angle gear box with 6 bolt flange blade carrier
- 3 bidirectional blades made with 5/8" AR400
- High torque motor with 3000 PSI relief valve

X-treme Brush Cutter Specs

